

LIME PAINT

Description

Mineral Life Int'l Lime Paint is an acrylic modified composition of the traditional coating with enhanced durability for application to most any building material. The character of natural limestone or color intrinsic concrete is easily achievable while maintaining high resistance to rain and solar UV radiation.

Uses

Mineral Life Int'l Lime Paint can be applied to the following vertical substrates:

1. Precast Concrete (after removal of release agent residue)
2. Exterior Stucco Plaster
3. Interior Drywall
4. Aluminum Window Frames
5. Steel Railings
6. Galvanized flashing
7. Wooden Doors and Moldings
8. Coating for Clay Roof Tile
9. Reactive with Mineral Life Int'l Mineral Patina Solutions for Antique Finishes.

Advantages

1. Hi strength bonding
2. Hi abrasion resistance
3. Excellent rain and efflorescence resistance
4. Repels water
6. Anti mildew, microbial without chemical fungicides
7. Can be applied over latex paint
8. Elastomeric bridging of hairline cracks
9. Scrubable
10. "Living Wall" character like Limestone. Brightens in color when wet, while maintaining color integrity when dry.
11. May be applied as a Lime Wash by mixing 1:1 with water for more variations of tone.

Primer

Stucco: 100% Acrylic Waterborne Masonry Sealer/Primer; Stucco must be a minimum of 2 weeks old before application.

Interior Drywall or Masonry Walls: Use only 100% acrylic exterior masonry primers/sealers.

Metals: Apply the appropriate metal primer for steel, aluminum or galvanized

Wood: Mineral Life Int'l Lime Paint can be applied directly to unsealed wood as a Lime Wash by cutting 1:1 with water, or, by using a 100% Acrylic Waterborne Primer and applying two coats.

Application

Application of Mineral Life Int'l Lime Paint can be made by **spray, lambswool roller** of 1 1/4 inch or 1 1/2 inch nap, short bristle **brush, or paint pad.**

You will see the **Lime Paint dry** as the color lightens.

Brush or roller strokes are applied as "sloppy brush", although fully coating the wall surface.

Two coats are recommended:

First Coat: Full Coat

Second Coat: Full Coat or a Wash Coat (1:1 with water).

Mineral Life Int'l **Patina Wash** is optional for an Antique Finish as a final application.

Technical Data

Density:1.25 - 1.38

Flash Point:.....No Flash Point

Colors:.....Mineral Life Int'l's

1. Classic Earthtones
2. Gemstone Colors
3. Southwestern Colors
- Custom Color Matching

Coverage:...

150 sq ft or 13.9 sq m / gallon depending on porosity and texture

Dilute:.....1. For a Lime Wash (1:1 with water)

MINERAL LIFE INT'L, INC. CORPORATE OFFICES

Tel: (011) 877-407-9510
(Fax: (011) 305-661-6942
Website: www.minerallife.com
e-mail: minlife@earthlink.net

SALES OFFICES

MIAMI, FL
Tel: (001) 305-661-9854
e-mail: minlife@earthlink.net
DUBAI, UAE
Tel: +971 80 558 1344
e-mail: uaecontact@minerallifeintl.com

LIMITED WARRANTY

Mineral Life Int'l warrants its products to be free of manufacturing defects and that they will meet Mineral Life Int'l's current published physical properties when applied in accordance with Mineral Life Int'l's directions. There are no other warranties by Mineral Life Int'l of any nature whatsoever, expressed or implied, including any warranty of merchantability of fitness for a particular purpose in connection with this product. Mineral Life Int'l shall not be liable for damages of any sort, including remote or consequential damages, resulting from any claimed breach of any warranty whether expressed or implied, including any warranty of merchantability of fitness for a particular purpose or from any other cause whatsoever.